PCT

08/609,776

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

G06K

(11) International Publication Number: WO 97/32274

(43) International Publication Date: 4 September 1997 (04.09.97)

US

(21) International Application Number: PCT/US97/03334

(22) International Filing Date: 3 March 1997 (03.03.97)

(30) Priority Data:

1 March 1996 (01.03.96)

(71) Applicant: FMR CORP. [US/US]; 82 Devenshire Street, Boston, MA 02109 (US).

(72) Inventors: LEIMAN, Oren, S.; 28 Breakneck Road, Groton, MA 01450 (US). MOSS, Clive, H.; Apartment 71, 7 Wainwright Road, Winchester, MA 01890 (US). AIELLO, Albert, Jr.; 81 Carisbrooke Road, Wellesley, MA 02181 (US).

(74) Agent: SHARKANSKY, Richard, M.; Fish & Richardson P.C., 225 Franklin Street, Boston, MA 02110-2804 (US). (81) Designated States: AU, CA, JP, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).


Published

Without international search report and to be republished upon receipt of that report.

(54) Title: OPEN SYSTEMS PRINTING

(57) Abstract

A method for open systems sprinting including routing print jobs automatically form different types of source computers to different types of printers without the source computers selecting printers for each print job. A method for open systems printing including routing print jobs automatically from an arbitrary number of source computers to an arbitrary number of printers without the source computers selecting printers for each print job. A method for printing including controlling the printing of print jobs on high-speed production printers through a graphical user interface. A print server for use with different types of source computers and different types of printers, the print server directs print jobs received from the source computers to the printers without the source computers



selecting printers for each print job. A print server for use with an arbitrary number of similar types of source computers and an arbitrary number of similar types of printers, the print server directs print jobs received from the source computers to the printers without the source computers selecting printers for each print job. An open systems printing environment including a source computer connected to a first network, a print server connected to the first network and a second network, an output manager connected to the second network, and a printer connected to the output manager, the print server directs print jobs generated by the source computer to the printer.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GR	Georgia	MX	Mexico :
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Paso	IB.	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KB	Kenya	RO	Romania
BY	Belama	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF.	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	K2	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	u	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
cs	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	T.I	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EB .	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
P	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MIR	Macritagia	VN	Viet Nam

OPEN SYSTEMS PRINTING

Background

This invention relates to open systems printing.

Printing is often a proprietary sub-system of
computer operating systems. This is especially true for
production or high-speed printing (i.e., greater than 100
pages per minute). For example, IBM MVS Mainframes 10, 12
(Fig. 1) are connected to IBM printers 14, 16 over IBM bus-and-tag channels 18, 20, Microsoft NT server 22 is
connected to NT printer 24 over proprietary bus 26, and
image server 28 is connected to image printers 30 over
proprietary busses 32. In a typical MVS environment, print
files are generated from a mainframe MVS application and
sent to a Job Entry Sub-System (JES). The print job is
routed over the proprietary bus to a printer directly
connected to the proprietary bus. The job is then printed
using JES commands.

10

15

25

When new processors are developed and installed, new printers corresponding to the new technology are also installed. Dedicated, high-bandwidth channel bus extenders are used to connect remote high-speed printers to a central mainframe location.

Client/server systems typically include smaller desktop computers (clients) connected to larger more powerful computers (servers). To print a client/server print stream on a high-speed printer, the print stream is typically routed (arrow 34) to a mainframe, e.g., MVS^m 10, and then routed to a high-speed printer, e.g., printers 14. The mainframe is effectively made a high-cost print server for the distributed client/server system.

Switch 36 enables either MVSTM 12 or a VAXTM mainframe 38 to send print streams to printer 40. If MVSTM 12 is configured to send print streams through switch 36 and a user instead wants to send print streams from VAXTM 38 to the printer, the user enables the VAXTM and disables the MVSTM and configures the switch accordingly. Approximately 20 minutes to an hour is required to re-configure the mainframes and switch. A new switch is needed to allow a different hardware platform, e.g., NTTM server 22, to share a printer with MVSTM 12 and/or VAXTM 38.

Summary

10

15

20

25

30

In general, in one aspect, the invention features a method for open systems printing including routing print jobs automatically from different types of source computers to different types of printers without the source computers selecting printers for each print job. In general, in another aspect, the invention features a method for open systems printing including routing print jobs automatically from an arbitrary number of source computers to an arbitrary number of printers without the source computers selecting printers for each print job.

Implementations of the invention may include one or more of the following. Routing may include sending the print jobs from the source computers to a print server and sending the print jobs from the print server to output managers connected to the printers. The print jobs may be sent from the source computers to the print server over a first network, e.g., a TCP/IP network, and the print jobs may be sent from the print server to the output managers over a second network, e.g., a local area network. The method may include transforming data in the print jobs into a format compatible with the printers, and the transformation may be carried out by the print server or an

output manager. After sending the print jobs from the source computers to the print server, the method may include storing the print jobs in a server spool coupled to the print server. Before sending the print jobs from the print server to the output managers, the data in the print jobs may be manipulated, for example, two print jobs may be merged into one print job. The method may also include printing the print jobs on paper, sending the print jobs to an electronic mail system, recording the print jobs on microfiche, and recording the print jobs on laser disk. Each of the print jobs may include at least two reports and routing may include sending the print jobs from the source computers to a print server and sending individual reports from the print server to output managers connected to the printers. After sending the print jobs from the source computers to the print server, the method may include bringing the source computers down for maintenance while printing the print jobs.

5

10

15

20

25

30

In general, in another aspect, the invention features a method for printing including controlling the printing of print jobs on high-speed production printers through a graphical user interface.

Implementations of the invention may include one or more of the following. The method may include receiving the print jobs at a print server coupled to the graphical user interface and listing the received print jobs in the graphical user interface. Controlling may include selecting a print job from the list of received print jobs, determining if a printer coupled to the print server has a set-up compatible with the selected print job's set-up, and sending the selected print job from the print server to an output manager connected to the printer. Selecting may include dragging-and-dropping the selected print job from

the list of print jobs onto a printer icon, and the method may also include preventing the drag-and-drop of the selected print job if the printer set-up is determined to be incompatible with the selected print job's set-up.

5

10

15

20

25

30

In general, in another aspect, the invention features a print server for use with different types of source computers and different types of printers, the print server directs print jobs received from the source computers to the printers without the source computers selecting printers for each print job. In general, in another aspect, the invention features a print server for use with an arbitrary number of similar types of source computers and an arbitrary number of similar types of printers, the print server directs print jobs received from the source computers to the printers without the source computers selecting printers for each print job.

Implementations of the invention may include one or more of the following. The print server may include an input receiver, coupled to the source computers, for receiving the print jobs from the source computers, a server spool, coupled to the input receiver, for storing received print jobs, a queue manager, coupled to the server spool and the input receiver, for directing each of the print jobs to a selected one of the printers through an output manager, and a data transformer, coupled to the server spool, for converting data in print jobs into a format compatible with the corresponding selected printers.

In general, in another aspect, the invention features an open systems printing environment including a source computer connected to a first network, a print server connected to the first network and a second network, an output manager connected to the second network, and a printer connected to the output manager, the print server

directs print jobs generated by the source computer to the printer.

Implementations of the invention may include one or more of the following. The open systems printing environment may also include a server spool coupled to the printer server and a graphical user interface coupled to the print server.

Advantages of the invention may include one or more of the following. Print streams generated on an arbitrary number of dissimilar/similar types of source computers, including client/server systems, are efficiently routed to an arbitrary number of dissimilar/similar high speed printing hardware. User application programs on source computers need not be modified, and the number of source computers and the number of printers is scalable. New technology (i.e., types of computers and printing hardware) is easily added to the printing system. Local print management provides cost effective operation of a large print center remote from a data center. A graphical user interface (GUI) provides a flexible, easy-to-use operator interface. Printing may continue when source computers are down for maintenance or due to failures.

10

15

20

25

30

Print streams generated by source computers may be manipulated in the open print server prior to being routed to available printing hardware. For example, bank statement data from a mainframe may be merged with image data (i.e., pictures of processed checks) from an image server before being routed to available printing hardware. Merging print streams in the open print server prior to printing reduces the handling required to process the merging of two print streams and reduces errors associated with known physical merging techniques.

Other advantages and features will become apparent from the following description, and from the claims.

Description

Fig. 1 is a block diagram of source computers directly connected to printers.

Figs. 2 and 3 are a block diagrams of an open systems printing environment.

Fig. 4 is a block diagram of the TCP/IP protocol stack.

10 Fig. 5 is a detailed block diagram of an open systems printing environment.

20

25

30

Figs. 6-31 are video screen displays of a graphical user interface to an open systems printing environment.

Referring to Fig. 2, an open systems printing 15 environment 50 includes an open print server 52 connected to source computers 54 through a Transmission Control Protocol/Internet Protocol (TCP/IP) network 56. The open print server receives print jobs from the source computers and efficiently routes the jobs over a local area network (LAN) 58 to various output managers 60. The output managers then have the jobs printed on directly connected printers 62.

TCP/IP is a communications protocol that was developed under contract from the United States Department of Defense in the 1970's to connect dissimilar computer systems. Today TCP/IP is a defacto standard after becoming the network protocol of choice for corporate data networks. TCP/IP is flexible and available on a wide range of hardware platforms. The protocol enables programmatic linking and routing of data between dissimilar computer systems. As a result, the open print server accepts print files from different hardware platforms, including IBM™ MVS™ mainframes 64 (Figs. 2 and 3), UNIX servers 66, Microsoft™ Windows NT™

servers 68, IBM^m AS/400 servers 70, and Digital Equipment Corporation^m VAX^m mainframes 72.

The highest level of TCP/IP is Application Layer 74 (Fig. 4). User level programming is incorporated at the top of the TCP/IP protocol stack at the Application layer. For example, File Transfer Protocol (FTP) is an application layer program. The Application Layer permits computers to connect to and work together over the network.

providing end-to-end reliability and sequencing of transmitted bytes of data. This ensures that each byte of data sent from a source computer is received correctly by the open print server. IP layer 78 of the TCP/IP protocol stack provides the routing mechanism / computer addressing information. Addressing information is used to forward bytes from source computers to the open print server.

Network Interface layer 80 defines the physical attributes of the network connection.

Many hardware platforms may serve as the open print server. For instance, the open print server may be a Sun™ SPARC™ 10/20 server 82 (Fig. 3), a Sun™ SPARC™ 1000 server 84, an IBM™ RS/6000 server 86, or a Hewlett Packard™ server Many output managers and printers are also available. The printers may be Advance Function Printing (AFP) in Page 25 or Line mode printers, intelligent printer data stream (IPDS) printers, impact, simplex, DUPLEX, line conditioned data stream (LCDS) and intelligent print stream (IPS), rollfed, sheet-fed, postscript, color, or continuous tone printers. For example, an output manager 90 including an ISI/OPS printer driver 91 may receive print jobs from the 30 open print server and direct them to IBM™ 3800-3 and 4245/8 printers 92, 94 and Siemens 2140/2240 page mode printers 96. Similarly, an output manager 97 including a PSF/6000

printer driver 98 may direct print jobs to IBM 3900, 3828/9, and 3900 duplex printers 100, 101, 102, an output manager 103 including a SNPS/8000 printer driver 104 may direct print jobs to Siemens™ 2140/2240 IPDS printers 105, Siemens[™] page stream printers 106, and Siemens[™] twin duplex printers 107, and an output manager 108 including a XEROX™ printer driver 109 may direct print jobs to a XEROX™ printer 110.

Referring to Fig. 5, an open printing client program 114 is installed on each source computer 116 to transfer print files from the source computers to open print server 52 over TCP/IP network 56 without modifying applications running on the source computers. As an example, source computer 116 is an IBM™ MVS™ mainframe. Application 118 running on the MVS mainframe transfers print files into a 15 Job Entry Sub-system (JES) which stores the print jobs on one or more MVS™ JES spools 120. Program 114 includes a JES2Q Program for each JES spool available to the MVS mainframe. Each JES2Q program searches a corresponding JES spool for print jobs having a destination identification (DESTID) corresponding to an open print server.

10

20

25

30

The JES2Q programs "strip" print jobs destined for the open print server from the JES spools, add open print server header information to the print jobs, and encapsulate the print jobs into TCP packets. The TCP packets are transferred to the open print server. The JES2Q programs interface with a TCP/IP stack 122 to pass print jobs to TCP/IP network routers via, for example, an IBM 3172 gateway 123 (Fig. 2). The routers send the print jobs over the TCP/IP network to an input receiver 124 on the open print server. The JES2Q programs communicate with the input receiver program through a sockets interface (program-to-

program) in the Application level of the TCP/IP protocol stack in a many-to-one relationship.

When the input receiver receives incoming print jobs, it writes the data onto a server spool 126 and uses the header information to log the job in a database, for example, a Sybase, Inc. database. Server spool 126 is a direct access storage device (DASD) and may include mirrored disks. The array contains, for example, four 16 gigabyte partitions which provide a total capacity of 64 gigabytes. File sizes may exceed the UNIX limit of 2 gigabytes. The input receiver notifies Queue Manager 128 of the status of all incoming print jobs.

10

15

25

Open print server error conditions, for instance, insufficient disk space or failed network lines, are communicated to the JES2Q programs on the MVS^{∞} mainframe through TCP/IP error codes. When the error condition is removed, e.g., disk space becomes available, the print job is restarted. Checkpoint restart capabilities allow the print job transmission to be re-initiated from the point of failure reducing the time required to finish the transmission.

The Queue Manager functions as a traffic cop by controlling the distribution of print jobs across the various printers. The Queue Manager forwards database update information to one or more Motif™ graphical user interfaces 130 (GUIs) through an operator application programming interface 132 (API). The GUIs provide print operators with a current view of the printing environment (discussed in more detail below). The Queue Manager also 30 processes commands received from the operator via the GUI and updates the database accordingly. The Queue Manager maintains Job accounting files and server log files and stores these files on the server spool. Job accounting

records 135 are generated in various formats, SMF included. These may be automatically sent to standard billing packages on other computers connected to the TCP/IP network.

While a print job is being received from a source computer, the Queue Manager accesses the print job's header information to determine which print resources are required to print the job and then accesses a resource manager 133 to determine if the required print resources are available. Print resources include fonts, coded fonts, overlays, page definitions, form definitions, page segments, FCBs, media maps, data maps, and graphics (e.g., logos and signatures). If a required print resource is not available, then the Queue Manager notifies the operator through the GUI. Similarly, the Queue Manager checks for a required printer set-up, for example, that a required form type is loaded, and notifies the operator if a required printer set-up is not available.

10

15

20

25

30

Using the GUI, a print operator selects a job in the server spool and directs the job to a specific printer. The Queue Manager initiates a data transformation (DTF) process 134 corresponding to the selected output manager and printer. The DTF process interrogates the job to determine, for example, if it is an AFP page or line mode job. The DTF process then reads the job from the spool, converts the data stream to, for example, a channel command word (CCW) format compatible with the target printer make/model, and writes the data back onto the spool. The DTF process also updates the database with status information and error condition messages, and this information is made available to the GUI through the Queue Manager.

After a sufficient amount of data has been properly transformed, the Queue Manager notifies the selected output manager that a print job is ready, and the output manager

begins reading the transformed portion of the print job from the server spool. For non-IPDS printers (i.e., Siemens¹⁰ 2140, 2240, IBM¹⁰ 3800, 4245), the output manager may be a Sun¹⁰ SparcClassic¹⁰ workstation with a printer adapter card to support the attached printer. For IPDS printers, the output manager may be an IBM¹⁰ RS/6000 workstation with PSF/6000 software or an OS/2 workstation with SNPS 8000 software and a Channel emulation card to support the attached printer. In the IPDS printing environment, the output manager reads data from the server spool that has not been transformed and completes the data transformation.

10

15

20

25

30

A programmer may generate data application programming interfaces 136 and corresponding DTF processes for manipulating data stored on the print server. example, many bank statements include data forms listing transactions and account status (accounting data) as well as image forms with graphical representations of processed checks (image data). In the past, these forms were either printed separately and physically merged together before being mailed to the account holder, or the image data was routed to a mainframe where the image data and account data was merged before being printed. Physically merging forms is error prone and may require substantial personnel time. Because image data files are generally large, routing image data to the mainframe may cause bandwidth problems in the network connecting the image server and mainframe requiring the installation of an expensive, high bandwidth bus. routing may also require a substantial amount of time. problem is multiplied if the mainframe is remote from the image server.

Through the open print server, data is routed once to the open print server where it is merged into one print job before being printed. After an image print job and an

accounting print job are stored in the server spool, the Queue Manager initiates a merge DTF through a merge data API to merge image and accounting data into one print job. An output manager corresponding to a printer capable of printing both data types is then notified of the print job.

LAN 58 (Fig. 5) and TCP/IP network 56 provide the open printing environment with scalability. Both networks permit many connections, for example, the LAN may have 256 connections. This allows additional source computers and output managers/printers to be easily connected to the environment when printing needs increase. Additionally, the environment may be updated with new technology, e.g., new source computers and output managers/printers, by generating corresponding open printing client programs 114 (Fig. 5) and DTF 134 processes.

10

15

Additionally, the TCP/IP network allows large print files to be easily and quickly transmitted from a data center of source computers to a remote print shop including the open print server, output managers, and printers. 20 Because print resources are stored on the open print server, print file transmissions are smaller and require less bandwidth. Once the files are transmitted, the source computers may be brought down for maintenance without interrupting the printers. Local printer management permits efficient use of printer time and capabilities, and because 25 the open print server routes print jobs across various printers, individual printers may be drained of print jobs and brought down for maintenance without bringing down the entire printing environment. Moving printer queue 30 management to the open print server may increase source computer performance by eliminating the need for such a function on the source computers. Source computers need not select, keep track of, or even know of available printers.

Printing/Operator Interface

The GUI provides an operator with complete control over printer management.

Referring to Fig. 6, the GUI includes a main status display 140 that allows the operator to manage the print operation, system configuration, and logging in and out of the system. In addition to standard Motif™ X-Windows™ features, the GUI includes features specific to the open print server. For example, source computer and printer icons 142, 144, respectively, are displayed and indicate through words 146 and the color of the icon the status of the corresponding device. For instance, a green printer icon indicates that the printer is active, paused, or draining, blue indicates that the printer is idle or drained, brown that the print driver is running but that the printer is unavailable, red that the print driver is unavailable, and yellow that operator intervention is required. Similarly, a green source computer icon indicates that the computer is active while a blue source computer icon indicates that the computer is idle.

10

15

20

25

30

The operator may double-click a left mouse button on a printer or client icon 142, 144, respectively, to cause additional information (e.g., forms, mode), specific to the corresponding device, to be displayed. A single-click of the right mouse button on a printer icon brings up a pop-up menu of printer functions including pause, resume, cancel job, drain, enable. The user may click the left mouse button on a printer function to cause the corresponding printer to execute that function.

Referring to Figs. 7 and 8, the operator may select a Printer Layout option 146 or a Client Layout option 148 from an Edit menu 150 to cause a Screen Layout Dialog box 152 or a Client Layout Dialog box 154, respectively, to

appear. The operator then uses the dialog boxes to select those printer and source computer icons to be displayed on the main status display window.

Referring to Fig. 9, the operator may select a Job Queue option 156 from a View menu 158 to cause a Job Queue Status table 160 to be displayed. The operator may then sort the Job Queue Status table display using options 162 (Fig. 10) in a Job Queue Status table View menu 164. These sort by options include class, priority, source, status, mode, name, form, criteria, or all jobs.

When the class option is selected, a class pop-up menu 166 (Fig. 11) of alpha codes from A through Z and numeric codes from 0 through 9 is displayed representing classes that the Job Queue Status table may be sorted on. The operator may then select one of these codes to sort the Job Queue Status table. When the priority option is selected, a Job View By Priority Selection Dialog box 168 (Fig. 12) is displayed. The operator may enter the priority on which he would like the Job Queue Status table sorted on. When the source option is selected, a source computer pop-up menu 170 (Fig. 13) is displayed from which the operator may select a source computer to sort the Job Queue Status table on, and when the status option is selected, a status pop-up menu 172 (Fig. 14) is displayed from which the operator may select a status to sort the Job Queue Status table on. Similarly, when the mode option is selected, a mode pop-up menu 174 (Fig. 15) is displayed, when the name or form options are selected, a Selection Entry dialog box 176 (Fig. 16), 178 (Fig. 17), respectively, is displayed, and when the criteria option is selected, a Criteria Display dialog box 180 (Fig. 18) is displayed through which the operator can select a combination of criteria, such as class and priority, to sort on. The operator may select the all jobs

15

20

25

30

option to cause all jobs to be displayed in the Job Queue Status table.

To perform an operation on a job, the operator selects the job in the Job Queue Status table by clicking the left mouse button on the desired job and selects the desired operation from the Operations menu 182 (Fig. 19). The operations include Hold, Release, Delete, Copy, Change Priority, Change Retention Time, Change Class, Print, and Report Queue. The Hold option allows the operator to put a print job on hold, and the Release option allows the 10 operator to change the status of a print job to ready. a print job has a ready status, the operator may print the job by selecting the print option and a desired printer from a Print Panel 184 (Fig. 20) or by moving the cursor over the job in the Job Queue Status table, pressing the left mouse 15 button down, and dragging-and-dropping the print job onto the desired printer icon (i.e., drag-and-drop technology). If the print job set-up does not match the printer set-up, for example, the form required for the print job is not 20 loaded on the printer, then the GUI indicates that the print job cannot be printed on the selected printer by not allowing the print option to be selected or by not allowing the print job to be dropped onto the printer icon.

Alternatively, the open print server may be configured to automatically print jobs with a ready status if a printer having a matching set-up is available.

25

30

If a job in a secure class is selected, a Security Authorization Dialog box 186 (Fig. 21) is displayed, and the operator must enter an authorized user name 188 and password 190 before an operation may be performed on the selected job.

Each print job may contain one or more reports
(i.e., smaller print jobs). When the report queue option is

selected, a Report Queue window 192 (Fig. 22) is displayed. The Report Queue window provides many of the same operational controls at the report level through an Operations menu 194 (Fig. 23) that are provided at the job level through the operations menu in the Job Queue Status Report operations include Hold, Release, Delete, Print, Resources, View Report Ticket, and Browse Report. The Hold, Release, Delete, and Print report operations work as described above with respect to print jobs. When the 10 Resources option is selected, a Resources Display window 196 (Fig. 24) is displayed. The Resources Display window shows a list of printer resources required to print the selected report. Each necessary printer resource also includes a status: Unchecked indicates that the Queue Manager has not 15 determined whether the resource is available in the resource manager; Missing indicates that the resource is not available through the resource manager; and Present indicates that the resource is available. Selecting the view report ticket option displays a Report Ticket window 20 198 (Fig. 25). The following information about a selected report is displayed: job name; data definition name; form used; print date; print start time; print end time; total lines in report; and total pages printed. An operator or a user connected to a source computer may add notes to a 25 report in a notes dialog box 200. For example, the user may add a note telling the operator where to send copies of each report. Selecting the Report Browser option displays a Report Browser window 202 (Fig. 26). The Report Browser window displays the actual contents of a selected report. 30

Referring back to Fig. 9, selecting the printer status option from the View menu of the Main Status Display window displays a Printer Status display window 204 (Fig. 27) including a one line status summary for each printer.

Through the printer set-up option in the View menu, the operator may configure available printers. When this option is selected, a pop-up menu 206 (Fig. 28) of available printers is displayed, and when a printer is selected from this menu or the operator double-clicks on the printer icon, a printer configuration dialog box 208 is displayed. The operator enters information into this dialog to configure the corresponding printer. Selecting the status log option causes a Status Log 210 (Fig. 29) to be displayed allowing the operator to view and search for recorded events.

10

15

20

25

30

System menu 212 (Fig. 30) includes a Print Resource option and a Spool Utilization option. Selecting the Print Resource option displays a Resource Dialog box 214. The Resource Dialog box displays existing resource directory paths for the selected printer and allows the operator to add and delete resource directory paths for the selected printer. Selecting the Spool Utilization option displays a Spool Utilization window 216 (Fig. 31). The Spool Utilization window displays the path name of each directory, the percentage of the total space currently used, total number of megabytes, total number of megabytes currently in use, total number of megabytes available for storage, and total megabytes for each column.

Reference to Microfiche Appendix

A microfiche appendix containing C language source code for open systems printing consisting of 1648 microfiche images on 17 microfiche cards is filed herewith. A portion of the disclosure of the patent document contains material which is subject to copyright protection. The copyright owners have no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or

records, but otherwise reserves all copyright rights whatsoever.

to a common TCP/IP network.

5

Other embodiments are within the following claims.

For example, multiple open print servers at locations remote from the source computers may be connected

As another example, the term "printers" as used in this specification refers to many different types of devices, including, but not limited to, paper printers, e-10 mail, computer output microfiche (COM) recorders, archival

systems, or computer output laser disk (COLD) recorders.

What is claimed is:

1

2

3

4

5

4

1

2 3

1 1. A method for open systems printing comprising: 2 routing print jobs automatically from different types of source computers to different types of printers 3 without the source computers selecting printers for each 4 5 print job.

- 2. A method for open systems printing comprising: routing print jobs automatically from an arbitrary number of source computers to an arbitrary number of printers without the source computers selecting printers for each print job.
- 1 3. The method of claims 1 or 2, wherein routing 2 includes:
- sending the print jobs from the source computers to 3 4 a print server; and
- 5 sending the print jobs from the print server to output managers connected to the printers. 6
- The method of claim 3, wherein the print jobs 1 are sent from the source computers to the print server over 2 a first network and the print jobs are sent from the print 3 server to the output managers over a second network.
 - 5. The method of claim 4, wherein the first network comprises a TCP/IP network and the second network comprises a local area network.
- The method of claim 3, further comprising: 1 2 transforming data in the print jobs into a format compatible with the printers. 3
- 7. The method of claim 6, wherein the data is 1 transformed by the print server. 2
- 1 The method of claim 6, wherein the data is 2 transformed by the output managers.

1 2

The method of claim 3, further comprising, after

```
sending the print jobs from the source computers to the
3
   print server:
           storing the print jobs in a server spool coupled to
4
   the print server.
5
                The method of claim 3, further comprising,
1
2
   before sending the print jobs from the print server to the
3
   output managers:
           manipulating data in the print jobs.
4
                The method of claim 3, further comprising
1
2
   before sending the print jobs from the print server to the
3
   output managers:
4
           merging at least two of the print jobs into a single
5
   print job.
               The method of claim 3, further comprising:
1
          printing the print jobs on paper.
2
1
                The method of claim 3, further comprising:
           sending the print jobs to an electronic mail system.
2
           14. The method of claim 3, further comprising:
1
2
           recording the print jobs on microfiche.
                The method of claim 3, further comprising:
1
          recording the print jobs on laser disk.
2
                The method of claims 1 or 2, wherein each of
1
   the print jobs include at least two reports and routing
2
3
   includes:
           sending the print jobs from the source computers to
4
   a print server; and
5
           sending individual reports from the print server to
6
   output managers connected to the printers.
7
                The method of claim 3, further comprising,
1
   after sending the print jobs from the source computers to
2
   the print server:
3
```

bringing the source computers down for maintenance while printing the print jobs.

- 1 18. A method for printing comprising:
- controlling printing of print jobs on high-speed production printers through a graphical user interface.
- 1 19. The method of claim 18, further comprising:
- 2 receiving the print jobs at a print server coupled
- 3 to the graphical user interface; and
- 4 listing the received print jobs in the graphical
- 5 user interface.

4

- 1 20. The method of claim 19, wherein controlling 2 further includes:
- 3 selecting a print job from the list of received
 4 print jobs;
- determining if a printer coupled to the print server has a set-up compatible with the selected print job's setup; and
- 8 sending the selected print job from the print server
- 9 to an output manager connected to the printer.1 21. The method of claim 20, wherein selecting
- 2 includes:
 3 dragging-and-dropping the selected print job from
 - the list of print jobs onto a printer icon.
- The method of claim 21, further comprising:

 preventing the drag-and-drop of the selected print


 job if the printer set-up is determined to be incompatible

 with the selected print job's set-up.
- 23. A print server for use with different types of source computers and different types of printers, the print server directs print jobs received from the source computers to the printers without the source computers selecting
- 5 printers for each print job.


24. A print server for use with an arbitrary number 1 of similar types of source computers and an arbitrary number 2 of similar types of printers, the print server directs print 3 jobs received from the source computers to the printers 4 without the source computers selecting printers for each 5 print job. 6 25. The print server of claims 23 or 24, 1 2 comprising: an input receiver coupled to the source computers, 3 the input receiver receives the print jobs from the source 4 computers; 5 a server spool coupled to the input receiver, the 6 server spool stores received print jobs; 7 a queue manager coupled to the server spool and the 8 input receiver, the queue manager directs each of the print 9 jobs to a selected one of the printers through an output 10 manager; and 11 a data transformer coupled to the server spool, the 12 data transformer converts data in print jobs into a format 13 compatible with the corresponding selected printers. 14 26. An open systems printing environment comprising 1 a source computer connected to a first network; 2 a print server connected to the first network and a 3 second network; 4 an output manager connected to the second network; 5 6 and a printer connected to the output manager, the print 7 server directs print jobs generated by the source computer 8 9 to the printer. 27. The open systems printing environment of claim 1 2 26, further comprising: a server spool coupled to the printer server. 3

28. The open systems printing environment of claim


- 2 26, further comprising:
- a graphical user interface coupled to the print
- 4 server.



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)









FIG.4




6/31



SUBSTITUTE SHEET (RULE 26)




SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)

FIG. 9



SUBSTITUTE SHEET (RULE 26)

10/31




FIG. 10


11/31

FIG. 11

⊕ •	_	Γ	몽	1	Ξ			Ξ			Ξ	Ξ			Ξ	Ξ		Ξ	Ξ		Ξ	Ξ			Ξ				_							_	Þ
•	Help		OWNER		nco3	CC 2	0007	0853316	UCC7	NF71574		_	_	٠.	ָ בַּיבָילָ בַּיבָילָ	֓֞֝֝֓֞֜֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	CCO	7220	CC7	רככת	UCC)	1000	CC7	רכט	0553316	0553316	220	IOTTPOI	IOFTPOI	1057701	FPAREAD	FPRREAD	FPRREAD	FPRREAD	UCC7	1035061	1000
			SOURCE	CPUS	9040	9040	9040	CPU6	9040	CPU6	9040	AWK1_SVR	AWHI_SVR	AWMZ_SVR			CPU6	CPU6	CPU6	CPU6	CPU6	CPU6	CPU6	CPU6	6PU6	t nan	CPUI	CPU6	CPU6	CPU6	CPU6	CPU6	CPU6	9040	ceu6	CPU6	CPU6
			TIME	06:36	23:10	91:40	07:43	22:16	05:38	06:40	05:09	1 2 4 5 6	04:24	W C		04:53	04:01	03:45	03:33	10:08	99:40	08:24	99:90	06:30	61:19	06:11	04:52	03:46	03:46	03:42	02:31	02:31	02:20	02:16	24:10	11:10	61:10
			QUEUE	92		:	=	12	12	_	- .	n (, n		• -	•		-	-	0	0	0	0	0	-			0	0	0	0	0	0	0	0	-	-
-			PRINTER MODE O	PAGE	LINE	TIME	LINE	PAGE	TINE	PAGE	LINE	PAGE	ADWA.	300	PAGE	PAGE	PAGE	PAGE	PAGE	PAGE	TINE	PAGE	PAGE	PAGE	and a	3549	PAGE	TINE	TINE	LINE	TINE	LINE	I.INE	LINE	LINE	2 .	רואנ
		Active Jobs	STATUS PR	READY	ногр	READY	READY	HOLD	READY	HOLD	HOLD	ACADI Caraci	XEAD!	#01.0#	HOLD	HOLD	HOLD	HOLD	HOLD	HOLD	HOLD	HOLD	HOLD	HOLD	25.274	НОГЪ	READY	READY	READY	READY	READY	READY	READY	READI	READY	200	neau:
		Current View -	PRINTED	0	599	0	0	2852	0	0 (.			1 9 9 9	1399	1299	1018	1899	1899	66	1790	29599	1099	763		1099	0	0	0	0 (> (.	> •		<i>></i> c	,	>
	ę	Curi	TOTAL	102135	11832	125	102	33915	3047	121	0480	• •	11336	81974	2247	11555	43086	52704	69818	2661	94791	2160	0011	34415	34415	17570	100222	23	: :				3306	36.00	7849	6234	
	afresh		H	26	_	_	_	_	m :	n o	n -	• -	•	. ~	-	88	7	~	96	m .		7 6			. ~	.	_	.			٠.	.	, r	, -			∦.
	_	ם כ			_		2	н	J.	×		10	2	2	0	å P	ত ম	17	, (A	2	.	5	7			₹ ;	, F	2	0		`		_	Ξ		9	
	View Operations	88	ority	801	∆ sn:				:		80	11.08	8071	1496	1496	1496	1496	1496	1496	1150	1010	7071	9071	STDI	STDI	1496	LSR	3101	1016	1016		125	1010	10.5	STD1	1506	
	View View	By Class	By Priority.	g By Source	Jd By Status	By Hode	7.0	JODY Neme.	JO By Porm.	criteria.	All Jobs	1080012	30800195	30801730	JOB06058	30800741	30807330	10807330	30803456	9511800	00121001	10811303	10804785	JOB 31307	30819839	10808326	JOB27646	JOB25717	1082143	10821195	10821110	10821212	JOB28842	1050FB0	30831317	JOB06489	
1	rile Edit		NAME NU	Il			•		SIMOABA			-		_	FBSIM47 3	-	-	•		Cabridae d				· ~	_			AROBENEO J								FBCFD14 JC	
			'									-												7	_	160	>				-	-					ال

SUBSTITUTE SHEET (RULE 26)

12/31



SUBSTITUTE SHEET (RULE 26)

13/31

Help Help UCCT UCCT UCCT UCCT UCCT TIME SOURCE 21:35 22:50 21:10 01:23 01:22 QUIUL QUEUE PRINTER MODE PRINTER MODE PAGE PAGE PAGE LINE OPServer Jab Queue Status Display-Covington TestServe OPServer Job Queue Status Display-Covington TestServer Source CPU1 Current View - All Jobs STATUS HOLD HOLD READY READY HOLD PRINTED Current View PRINTED 1019 PRI TOTAL AWH1_SVR AWH2_SVR AWM3_SVR AHM_SDR CPU1 Refresh C TESTNT OPSSRV Refresh OPS1A PRI CPU2 CPU6 CPU7 View Operations Operations FORMS Criteria. . . 87D1 1491 STD1 STD1 STD1 STD1 Jo By Status Jo By Mode Jo By Name... Jo Criteria... Jo All Jobs Priority By Priority By Source By Class JOB23901 View NUMBER Edit 164 Edit FDALOBGA FNASDBOC FMED114 FPRSDBOA FUNDBOA FTCINDBOA FTSTOPSED FROD SRVCOVZF FNAD174 FNASD80C FMED174 FPRSD80A FBDN006 SRVCOV2F FNAD127 FNAD174 FCID174 FCID174 FCID174 ri le F116 NAME П 160 160

SUBSTITUTE SHEET (RULE 26)

14/31


FIG. 14

H	۵		OWNER			_				.=	7.	_	_	-	Ĩ	_	_	_	_	_		1			<u> </u>	Ī	18	5 L	_	_	_	_	_
ľ	Help		8	ž	083	DSS	• BX	• BX		280	¥8.	083	085	. DS\$	D89	280	• 87	¥B.	¥ .	2	ě			f	֓֞֟֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֟֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֟֓֓֓֓		2330		*8*	ă.		080	3
			SOURCE	Cpuk	FITE	PITE	FITE	FITE	F178	FITE	FITE	PITE	FITE	FITE	FITE	rite	FITE	211	FITE		111						Sottone		FITE	217		2116	
			THE	9:35		17:34	23:44	23:44	23:44	23:44	23:43								22:45		_			1			FINE			21:30	ł		
			20200	-	-	-	8	۰ ۱	n 5	2	2	2	2	2	2	2	2	, .	, ,	2	2			ı			OUEUE		62 6	3		2,6	
			MODE	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	PAGE	PAGE	LINE	TINE	CINE	LINB	LINE	LINE	LINE	LINE	LINE	ZINE	ZNI.	2217	LINE	LINE	TINE						MODE		3 2 2 2	LINE		LINE	
			PRINTER																								PRINTER M		i.			ដ	•
À		sq	A.	0	\$	\$		٥ ()	0	•	0					٥ () ()	\$	•					Sqo	PRI	K	(10		;	;
OPS Gueue Menager Status Display-Embassy		Active Jobs	STATUS	READY	READY	READT	NCOMING	INCOMING HOLD	READY	HOLD	Q'TOH	READY	READY	MCOMING	READY	I MCOMING	READI	1000	READY	ADY	READY			OPS Queue Manader Status Dishlau, Emhassa		Inconing Jobs	STATUS	CNIMOUNT	ONTHO	INCOMING	INCOMING	INCOMING	**********
etus Dis			81	R	X	4	2 :	ž 9	2	웊	꾶	2	æ .	2 1	Z :	Z 1	X 0		z es	8	R			itus Die		Inco	STA	1 2	CAL	IN	INC	IN	
rager St.		Current View	PRINTED																					ager Sta		lew -	PRINTED						
PU ME		urrent	æ	0	۰,	0	0 0	-	0	0	0	۰ ۰	B (0 (o 0				•	0	•			Ne Man		Current View	PRI		0	0	0	0	c
0P8 Qu		٥	TOTAL	218286		<u>_</u>					Di	7	129	٠,	• -	. 5	3 5		193	129	30			OPS Ou		Curi	TOTAL	35	33	1			_
	Refresh		R	-	1	Tucour.	Ready	PTOR	Active	Completed	Printing	٤	2 6) (, s			7	. 6	90	6				Refresh		PRI 1	99			95	88 1	_
	Ť	Δ	<u>!</u>	Δ	A.		ž :	ž,	ž (<u>ម</u>	֡֟֟֟֟֟֟֟	֡֝֞֝֞֝֞֝֓֞֝֟֝֟֝֟֝֟֝֟֝֟֟֝֟֝֟֝֟֟֝֟֟֝֟֟֝֟֟֝ <u>֚</u>	4 1	< >	4 b	. «	. <	×	×	×	1	_	172				CLS	~	×	×	×	×	4
	Operations		Priority	90	us		نه	و در				8101	1010	10.5	1012	STD1	STD1	STD	STD1	8101	STDI		_		Operations		FORMS	STDI	STDI	STDI	STDI	STDI	STO
	View	By Class	/ Prio		Status	/ Mode	Name.		Criteria.	30 A		7 0 0 0	1000	200	35.76	1528	7847	9278	9501	1090	9				View Op								
-	Edit.		NU By	JO BY	30 BY	81 By		STB	<u>ار</u> ام	S	15	20180C	1001000	30810603	30810576	STC07528	STC07847	STC09278	STC09501	JOB10601	STC01116						NUMBER	JOB	308	308	308	308	BOC
			2	08829508	SPOOLISE	A6022680	OPSEMB	OPSEMB	OPTEST2	OPTEST8	OPSEMB	1163140	0153130	077770	OPTEST3	OPSEMB	OPSEMB	OPSEMB	OPSEMB	OPTEST6	OFSERB				e <u>E</u> dit		22	OPSEMB	OPSEMB	OPSTEST9	OPSTEST3	OPSTEST7	23/60
H:	ĝ.		ZHYN	088	286	200	200	7	8		200	3 8	5 8	à	- 6	008	008	063	98	ő	5			1	£116		NAME	OPS	S	240	98	000	120
					(2) /	/																					200	/	/		


SUBSTITUTE SHEET (RULE 26)

15/31


FIG. 15



SUBSTITUTE SHEET (RULE 26)




SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)

18/31



SUBSTITUTE SHEET (RULE 26)


19/31

FIG. 19

	1170 2011													
	1		Descentions	_	2012									Fe la
(PIQ				cent View	- Active J	Jobs			Ý		
182	HAME	MUMBER	Release				PRINTED	STATUS	PRINTER	HOTE	QUEUE	E TIME	SOUNCE	DENER
	ANHAGE	30800124	Pelete.	:			1,1	HOLD		PAGE	=	00:18	AWH2_SVR	Y
	FCINDSOA		Copy				21.16	HEAD!		NO E	= :	06:18	9040	ğ
	FMEGD81		Change Priority	Prior	ity.					2 6	: :	70.6	9040	
(PCINDBI		Change Retention Time.	Reten	tion	Time		ROLD		PAGE	=	23:00		֝֓֞֝֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓
	FRASD81	7	Change Class	Class		Δ	0	READY		PACE	=	23:00		ÿ
	PCINDBI		Print	١,			_	HOLD		PAGE	Ξ	13:00	9040	ğ
J	LOYCOL	30823443					2	HOLD		PACE	Ξ	35:28	9040	C)
	L KEDI JA		Taper.		ا		-	HOLD		PAGE	Ξ	22:51	CPUE	ğ
	FWAD127	30819617	5101	••	-	6211		KOLD		LINE	=	04:41	\$nab	5
	TAYOL Y	20830706		•• (~	1		200		PAGE	2	03:11	CPUI	CCC
	10101	2007 1000		* *	n •	6613		READY		NO I	2 :	03:01	CPU6	ğ
	1		1	╬		7.5	,	COOR		1	2	22:00	9040	ğ
		2005	200	-	-	2000	1135	READY		100	=	02154	9040	DCC.
		16767800		.	~ .	21811		ğ		MGE	2	01:53	9040	000
	CHASDOOL	07911607		H	٠,	1287	10368	970		M CE	2	01:28		ğ
		0.00000		- (•	200		ACTOR MOTOR		300	2	11:0	CPUI	ğ
	FFKSOBOA	2000	1491	H	~	65 81	0	READY		BYGE	2	01:09	CPUI	ğ
	MORGINA	20823802		*	~		1019	3		MGE	•	05:41	CPU6	ğ
	TAKORA	30811725	1491	2	~	4 12	•	BOLD		PAGE	-	01:20	CPOS	8
	,				E	D dot was	OPServer Job Queue Status Dis	olay-Covington TestSarver	Contanyor	ı	l			F
	File Edit	Viov	Operations		Refresh									활
										l	ļ			
						3	CULTERE VIEW	ACCIVE JODS	2					
	Z.NE	NUMBER	PORMS	3	Ë	TOTAL	PRDTED	STATUS	PRDATER	HODE	QUEUE	2 THE	SOURCE	OWNER
	AWM3GB	30800124	SDTI	U	_	00099	-1	GTOR		PAGE	≂	00:15	AWA2 SVR	Ä
	FPR0174	30812155	1491	_	~	1206	1302	READY		PAGE	=	96.18		1
	PCINDBOA	30818838	1491	•	-	1165	2110	KOLD		PAGE	=	23.01	9130	֓֞֝֜֜֜֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓
	FMECD81	30827384	1691	۳	_	1:	•	400		PACE	Ξ	23:00		֓֞֝֓֞֜֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓
	FCINDSI	30826827	-	H	_	=	•	8070		PACE	Ξ	23:00	_	
	LINASDEL	9280C	=	•	~	110	0	READY		PAGE	=	23:00		0
150	ICINDS!	30827384	=	-	~	1:3	0	9708		PAGE	Ξ	23:00		5
<u> </u>	LOACOSI	30825445	1691	٠	~	=		ROLD		PACE	Ξ	22:56		
/	FMEDIA	30825598	149	H	-	2012	0	ROLD		PAGE	Ξ	22:51		5
J	FNAD127	1961802	404	⊷	-	1467	0	ROLD		LINE	=	04:41	9040	Coo
	LINADIA	30830704		6- 1	~	=	•	ROLD		PAGE	2	03:11	CPUI	200
		76877900	160	- 1	•	2135	•	READY		PACE	2	03:01	9040	5
	- 1	10801 109		-	~	1699	0	HOLD		PAGE	2	03:00		5
		30828332		-	-	30482	1135	READY		PAGE	2	02150	1	S
		16765900		,	~	11312	0	MOCO		PAGE	2	01:53	ı	CCC
	DOBOSWA	07811800		••		12574	10568	HOLD		FACE	2	01:28	CFUI	נוככו
	S CALLES	0.070805	6)	~	1572	•	HOLO		PAGE	2	1:10	CPUI	500
	VOSCIAL DE	30823410	167	•	~	1139	0	READY		PAGE	2	03:09	CPU1	CUD
	E	10863805	7 6 6 7	.	•		6101	#OF			•			
•	FPDCDBOR	100111736	. 70.	:							-		200	ğ

SUBSTITUTE SHEET (RULE 26)

20/31



SUBSTITUTE SHEET (RULE 26)

21/31





FIG. 21

22/31


FIG. 22




SUBSTITUTE SHEET (RULE 26)

MBER E CLS STATUS MODE TOTAL 082	Help
082 T COMPLETED 089 T HOLD 096 T READY 103 T READY 114 T FOREY	TED PRINTER RPT 10
089 I HOLD 096 I READY 103 I READY 134 I READY xt Ticket	60200
096 T READY 103 T READY 134 T READY FT Ticket	50128
103 T READY 134 T READY of Ticket 141 T Despe	25200
Ticket 1141 t seed	38280
>4140 + L71	63312
	49328
Browse Report 150 t READY	15088
IIST T READY	33712


SUBSTITUTE SHEET (RULE 26)




SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)




SUBSTITUTE SHEET (RULE 26)




SUBSTITUTE SHEET (RULE 26)

28/31




SUBSTITUTE SHEET (RULE 26)


29/31



SUBSTITUTE SHEET (RULE 26)

30/31





SUBSTITUTE SHEET (RULE 26)